

## Terminal horquilla

### *Open Swaged Fitting*

Número de certificación  
Approval-Number  
Z-14.7-413


**PG** Tipo  
*Type* 980



Material:  
according Technical Approval Z-14.7-413

**Corrosion Protection:**  
hot dip galvanized 80 µm DIN EN ISO 1461/  
spraying galvanized

### Spiral strands



Tamaño size										Placa de anclaje/connecting plate Material/material: S 355				Peso total* tot.-weight*	
	A mm	B mm	C mm	D <sub>max</sub> * mm	D <sub>b</sub> mm	E mm	F mm	G mm	~L <sub>V</sub> * mm	d <sub>L</sub> mm	t <sub>L</sub> mm	a <sub>min</sub> mm	c <sub>min</sub> mm	kg	d <sub>s</sub> mm
PG 5	33	12,5	25	16	12	24	20	36	137	13	10	14	10	0,3	8,1
PG 10	43	14,5	30	20	15	29	25	41	170	16	12	17	12	0,6	10,1
PG 15	51	17,5	37	25	19	35	30	48	205	20	15	22	15	1,0	12,2
PG 20	61	20,5	42	30	22	41	35	55	240	23	18	25	17	1,6	14,1
PG 25	69	22,5	48	34	25	48	41	61	283	27	20	29	20	2,5	17,0
PG 40	84	28,0	59	40	30	58	49	74	343	32	25	34	24	4,8	20,1
PG 55	103	28,0	70	50	33	66	60	87	411	35	25	41	30	9,1	24,4
PG 75	119	33,0	82	57	40	76	69	99	480	42	30	48	34	12,5	28,3
PG 90	128	38,0	87	64	45	84	74	108	521	47	35	51	36	18,0	31,3
PG 125	152	49,0	105	71	55	101	89	126	616	57	45	63	44	25,5	36,3

\*after swaging  
Dimensions without corrosion protection  
Subject to technical modification