





[Home](#) > [Product Search](#) > [Product Parameter](#) > Single-ended


















Single-ended

-  [General Technical Information](#)
-  [Material Data Sheets](#)

Hitlist

Please note that online our ordering codes have changed to 15 digits.
This does not affect the technical specifications of our components. The data sheets will be changed step by step.
Number of hits: 17

-  Only Types available from Stock
-  Only Withdrawn Products

PDF	Offered by distributor	Rated voltage V	Capacitance μ F	Capacitance tolerance %	Max. equivalent series resistance, 120 Hz, 20°C mOhm	Rated ripple current "120 Hz, upper cat, temp, " A	Diameter mm	Length mm	Lower category temperature °C	Upper category temperature °C	Useful life (at upper cat. temp) h	Remarks	Type	Ordering code	Withdrawn Product
		35	33	\pm 20	7000	0.085	5	11	40	85	2000	General purpose, standard series	B41821	B41821A7336M000	
	show	35	47	\pm 20	4900	0.13	5	11	40	85	2000	General purpose, standard series	B41821	B41821A7476M000	
		35	68	\pm 20	3400	0.16	6.3	11	40	85	2000	General purpose, standard series	B41821	B41821A7686M000	
		35	100	\pm 20	2300	0.18	6.3	11	40	85	2000	General purpose, standard series	B41821	B41821F7107M000	
		35	150	\pm 20	1500	0.27	8	11	40	85	2000	General purpose, standard series	B41821	B41821A7157M000	
	show	35	220	\pm 20	1100	0.39	10	12.5	40	85	2000	General purpose, standard series	B41821	B41821A7227M000	
		35	270	\pm 20	900	0.43	10	12.5	40	85	2000	General purpose, standard series	B41821	B41821A7277M000	
		35	330	\pm 20	700	0.45	10	12.5	40	85	2000	General purpose, standard series	B41821	B41821A7337M000	
	show	35	470	\pm 20	490	0.65	10	16	40	85	2000	General purpose, standard series	B41821	B41821A7477M000	
		35	560	\pm 20	410	0.77	10	20	40	85	2000	General purpose, standard series	B41821	B41821A7567M000	
		35	680	\pm 20	340	0.84	10	20	40	85	2000	General purpose, standard series	B41821	B41821A7687M000	
	show	35	1000	\pm 20	230	1.25	12.5	25	40	85	2000	General purpose, standard series	B41821	B41821A7108M000	
		35	1500	\pm 20	150	1.4	16	25	40	85	2000	General purpose, standard series	B41821	B41821A7158M000	
		35	2200	\pm 20	120	1.8	16	25	40	85	2000	General purpose, standard series	B41821	B41821F7228M000	
		35	3300	\pm 20	90	2.15	18	31.5	40	85	2000	General purpose, standard series	B41821	B41821A7338M000	
		35	4700	\pm 20	70	2.3	18	40	40	85	2000	General purpose, standard series	B41821	B41821A7478M000	
		35	6800	\pm 20	60	2.5	22	40	40	85	2000	General purpose, standard series	B41821	B41821A7688M000	

 [back](#)

This page and its contents are covered by copyright © 2001 EPCOS.
[Published by](#) [Terms of usage](#)

